



DRAWN BY:		DATE:					
AO 12/11/18							
APPROVED BY:		DATE:		TITLE: CP1377-C-2 SIMPLEX CONTROL SCHEMATIC			
THIS DRAWING CONTAINS PROPRIETARY INFORMATION AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN AUTHORIZATION.				SIZE	DWG NO.	PART NO.	REV
				B	761	CP1377-C-2	D
				SCALE	NONE		SHEET

FNAME: CP1377-C-2

REVDATE: 0419





DASHED LINE INDICATES  
FIELD WIRING.

USE COPPER CONDUCTORS ONLY.  
TEMPERATURE RATING OF CONDUCTORS IS TO BE 60°C (167°F).  
BRANCH CIRCUIT PROTECTION SHALL BE PROVIDED BY THE  
INSTALLER: MUST BE SIZED ACCORDING TO PUMP/MOTOR  
MANUFACTURING SPECIFICATIONS.  
VERIFY CORRECT OPERATION OF CONTROL PANEL AFTER  
INSTALLATION IS COMPLETE.

REVISIONS				
ZONE	REV	DESCRIPTION	DATE	APPROVED
	A	REMOVED TB1	2/05/19	
	B	UPDATED WIRING	2/19/19	
	C	UPDATED FIELD WIRING CONNECTION LABELS AND SUPPLY VOLTAGE	3/12/19	
	D	REVISED FELX-PRO T7 WIRING & LABEL	4/17/19	

FIELD WIRING CONNECTIONS



DRAWN BY:		DATE:			
AO 12/11/18					
APPROVED BY:		DATE:		TITLE:  CP1377-C-2 SIMPLEX CONTROL SCHEMATIC	
THIS DRAWING CONTAINS PROPRIETARY INFORMATION AND SHALL NOT BE USED OR DISCLOSED WITHOUT PRIOR WRITTEN AUTHORIZATION.					
		SIZE B	DWG NO. 761	PART NO. CP1377-C-2	REV D
		SCALE NONE		SHEET 2 OF 2	